



TEXAS DEPARTMENT OF WATER RESOURCES

REPORT 225

ANALYTICAL STUDY OF THE OGALLALA AQUIFER
IN DAWSON AND BORDEN COUNTIES, TEXAS
Projections of Saturated Thickness, Volume of Water in Storage,
Pumpage Rates, Pumping Lifts, and Well Yields

By

Ann E. Bell and Shelly Morrison

November 1978

TEXAS DEPARTMENT OF WATER RESOURCES

Harvey Davis, Executive Director

TEXAS WATER DEVELOPMENT BOARD

A. L. Black, Chairman
Milton Potts
John H. Garrett

Robert B. Gilmore, Vice Chairman
George W. McCleskey
Glen E. Roney

TEXAS WATER COMMISSION

Felix McDonald, Chairman

Dorsey B. Hardeman, Commissioner
Joe R. Carroll, Commissioner

Authorization for use or reproduction of any original material contained in this publication, i.e., not obtained from other sources, is freely granted. The Department would appreciate acknowledgement.

Published and distributed
by the
Texas Department of Water Resources
Post Office Box 13087
Austin, Texas 78711

FOREWORD

Effective September 1, 1977, Texas three water resources agencies, the Texas Water Rights Commission, the Texas Water Development Board, and the Texas Water Quality Board, were consolidated to form the Texas Department of Water Resources. A number of publications prepared under the auspices of the predecessor agencies are being published by the TDWR. To effect as little delay as possible in production of these publications, references to these predecessor agencies will not be altered except on their covers and title pages.

A handwritten signature in cursive script that reads "Harvey Davis". The signature is written in black ink and is positioned above the printed name and title.

Harvey Davis
Executive Director

TABLE OF CONTENTS

	Page
CONCLUSIONS	1
INTRODUCTION	1
PURPOSE AND SCOPE OF STUDY	2
NATURE OF THE OGALLALA AQUIFER	3
General Geology	3
Storage Properties	4
Natural Recharge and Irrigation Recirculation	4
PROCEDURES USED TO OBTAIN PROJECTIONS	4
Hydrologic Data Base	4
Projecting the Depletion of Saturated Thickness	5
Mapping Saturated Thickness, and Calculating Volume of Water in Storage	7
Calculating Pumpage	8
Calculating Pumping Lifts	9
Well-Yield Estimates	9
DISTINCTION BETWEEN PROJECTIONS AND PREDICTIONS	10

TABLES AND MAPS PRESENTING RESULTS OF THE STUDY

SATURATED THICKNESS AND VOLUME OF WATER IN THE OGALLALA AQUIFER	11
Tables of Volume of Water in Storage Corresponding to Mapped Saturated-Thickness Intervals, 1974	12
Map Showing Estimated Saturated Thickness, 1974	13
Tables of Volume of Water in Storage Corresponding to Mapped Saturated-Thickness Intervals, 1980	14
Map Showing Projected Saturated Thickness, 1980	15

TABLE OF CONTENTS (Cont'd.)

	Page
Tables of Volume of Water in Storage Corresponding to Mapped Saturated-Thickness Intervals, 1990	16
Map Showing Projected Saturated Thickness, 1990	17
Tables of Volume of Water in Storage Corresponding to Mapped Saturated-Thickness Intervals, 2000	18
Map Showing Projected Saturated Thickness, 2000	19
Tables of Volume of Water in Storage Corresponding to Mapped Saturated-Thickness Intervals, 2010	20
Map Showing Projected Saturated Thickness, 2010	21
Tables of Volume of Water in Storage Corresponding to Mapped Saturated-Thickness Intervals, 2020	22
Map Showing Projected Saturated Thickness, 2020	23
POTENTIAL WELL YIELD OF THE OGALLALA AQUIFER	25
Map Showing Estimated Potential Yield, 1974	27
Map Showing Projected Potential Yield, 1980	28
Map Showing Projected Potential Yield, 1990	29
Map Showing Projected Potential Yield, 2000	30
Map Showing Projected Potential Yield, 2010	31
Map Showing Projected Potential Yield, 2020	32
PUMPING LIFTS IN THE OGALLALA AQUIFER	33
Tables of Surface Area Corresponding to Mapped Pumping-Lift Intervals, 1974	34
Map Showing Estimated Pumping Lifts, 1974	35
Tables of Surface Area Corresponding to Mapped Pumping-Lift Intervals, 1980	36
Map Showing Projected Pumping Lifts, 1980	37
Tables of Surface Area Corresponding to Mapped Pumping-Lift Intervals, 1990	38
Map Showing Projected Pumping Lifts, 1990	39

TABLE OF CONTENTS (Cont'd.)

	Page
Tables of Surface Area Corresponding to Mapped Pumping-Lift Intervals, 2000	40
Map Showing Projected Pumping Lifts, 2000	41
Tables of Surface Area Corresponding to Mapped Pumping-Lift Intervals, 2010	42
Map Showing Projected Pumping Lifts, 2010	43
Tables of Surface Area Corresponding to Mapped Pumping-Lift Intervals, 2020	44
Map Showing Projected Pumping Lifts, 2020	45
PUMPAGE FROM THE OGALLALA AQUIFER	47
Tables of Pumpage Corresponding to Mapped Decline-Rate Intervals, 1974	48
Map Showing Estimated Rates of Water-Level Decline, 1974	49
Tables of Pumpage Corresponding to Mapped Decline-Rate Intervals, 1980	50
Map Showing Projected Rates of Water-Level Decline, 1980	51
Tables of Pumpage Corresponding to Mapped Decline-Rate Intervals, 1990	52
Map Showing Projected Rates of Water-Level Decline, 1990	53
Tables of Pumpage Corresponding to Mapped Decline-Rate Intervals, 2000	54
Map Showing Projected Rates of Water-Level Decline, 2000	55
Tables of Pumpage Corresponding to Mapped Decline-Rate Intervals, 2010	56
Map Showing Projected Rates of Water-Level Decline, 2010	57
Tables of Pumpage Corresponding to Mapped Decline-Rate Intervals, 2020	58
Map Showing Projected Rates of Water-Level Decline, 2020	59
ACKNOWLEDGEMENTS	60
STAFF INVOLVEMENT	60

TABLE OF CONTENTS (Cont'd.)

	Page
METRIC CONVERSIONS TABLE	60
SELECTED REFERENCES	61

ANALYTICAL STUDY OF THE OGALLALA AQUIFER IN DAWSON AND BORDEN COUNTIES, TEXAS

Projections of Saturated Thickness, Volume of Water in Storage, Pumpage Rates, Pumping Lifts, and Well Yields

CONCLUSIONS

The Ogallala aquifer in Dawson and Borden Counties contained approximately 3.8 million acre-feet (4.7 km^3) of water in 1974. Historical pumpage has exceeded 90,000 acre-feet (0.11 km^3) annually, which is more than twice the rate of natural recharge to the aquifer in the counties. This overdraft is expected to continue, ultimately resulting in reduced well yields, reduced acreage irrigated, and reduced agricultural production.

In some areas the resource is adequate and will continue to support current usage through 1990; whereas, in some areas, ground water is currently in short supply. In much of the area, declining water levels and reduced saturated thicknesses will result in declining pumping rates and the expansion of the extent of those water-short areas.

To obtain maximum benefits from the remaining ground-water resources, water users should implement all possible conservation measures so that the remaining ground-water supply is used in the most prudent manner possible and with the least amount of waste.


INTRODUCTION

Dawson and Borden Counties are situated in the Southern High Plains of Texas. Lamesa, the county seat of Dawson County, and Gail, the county seat of Borden County, are located approximately 60 miles (96 km) south and 75 miles (121 km) southeast of Lubbock, respectively. The counties have a total population of approximately 17,000 and contain a total area of about 1,809 square miles ($4,685 \text{ km}^2$), of which approximately 800 square miles ($2,072 \text{ km}^2$) lies west of a prominent escarpment which forms the eastern boundary of the Texas High Plains. This report deals

with that area of the counties above the escarpment which is underlain by the Ogallala Formation.

Dawson and Borden Counties are two of the leading producers of agricultural crops in the State with a total farm income of over \$58 million annually. Leading crops in these counties are cotton, grain sorghums, wheat and other grains. Numerous agribusinesses, including livestock feeding, cotton and grain sorghum industries, food processing, and sale of irrigation equipment supplies, feed and seed, and fertilizer, also make significant contributions to the total county incomes.

Ground water is extremely important to the economy of the area inasmuch as most of the crops are irrigated with ground water. Additionally, the water



Location of Dawson and Borden Counties, and Extent
of the Ogallala Aquifer in Texas

used by rural residents, municipalities, and local industries is mostly ground water.

The principal source of fresh ground water in the area is the Ogallala aquifer. During the past three decades, the withdrawal of ground water has greatly exceeded the natural recharge to the aquifer. If this overdraft continues, the aquifer ultimately will be depleted to the point that it may not be economically feasible to produce water for irrigation.

This is one of numerous planned county studies covering the declining ground-water resource of the Ogallala aquifer in the High Plains of Texas. The report contains maps, charts, and tabulations which reflect estimates of the volume of water in storage in the Ogallala aquifer in Dawson and Borden Counties and the projected depletion of this water supply by decade periods through the year 2020. The report also contains estimates of pumpage, pumping lifts, and other data related to current and future water use in the counties. However, the report does not attempt to project that portion of the volume of water in underground storage which may be ultimately recoverable.

PURPOSE AND SCOPE OF STUDY

This study resulted from an immediate need for information to illustrate to the High Plains water users that the ground-water supply is being depleted. It is hoped that this study will help persuade the water users to implement all possible conservation measures, so that the remaining ground-water supply will be used in the most prudent manner possible and with the least amount of waste.

The study was also conducted to provide information to local, State, and federal officials for their use in implementing plans to alleviate the water-shortage problem in the High Plains of Texas.

These immediate needs for current information have resulted in a concerted effort by the Texas Department of Water Resources to utilize high-speed computers to conduct evaluation and projection studies of ground-water resources. The results of one of these computer studies is contained in this report.

This report does not represent a detailed ground-water study of the two counties; rather, the report was prepared using only those data which were readily available in the files of the Texas Department of Water Resources. Information provided for 1974 is considered reliable; however, the projections of future

conditions should be used only as a guide to reasonable expectations.

This study represents a new approach by the Department in making and presenting appraisals of ground-water resources. Consequently, a detailed explanation of the methods and assumptions used in the study is included. A complete set of tabulations and illustrations resulting from this study is presented at the end of the report.

The illustrations were prepared to answer four questions believed to be of prime importance to the Dawson and Borden County landowners and water users. These questions, and methods by which a set of answers can be obtained from the illustrations, are as follows:

1. Question: How much water is in storage under any given tract of land and what is expected to happen to this water in the future?

Answer: First, determine the approximate location of the tract on the most current (1974) map of saturated thickness. Read the value of the contour line at this location (if midway between two contour lines, take an average of the two). This thickness value can then be converted to the approximate volume of water in storage, in acre-feet per surface acre, by multiplying it by the coefficient of storage of 0.15, or 15 percent. To obtain estimates of what can be expected in the future, the same procedure can be followed by using the maps which illustrate projected saturated thickness in the years 1980, 1990, 2000, 2010, and 2020.

2. Question: What can be expected to happen to well yields if the saturated thickness diminishes as illustrated by the maps?

Answer: Well yields are expected to decline as the aquifer thins; therefore, a map of estimated well yields has been prepared for each year of the study. The landowner need only find the approximate location of his property on the well-yield map that applies to the year in question and read the well-yield estimates directly from the map.

3. Question: With energy cost increasing, pumping lifts (pumping levels) are becoming more and more important. What are the estimates of current pumping lifts

and what are they expected to be in the future?

Answer: Contour maps depicting estimated pumping lifts have been prepared for each year of the study. These maps are contoured in feet below land surface. The landowner need only find the approximate location of his property on the map that applies to the year in question to read the pumping-lift estimates.

4. Question: If an all-out effort is made to conserve ground-water resources, how can landowners and water users determine how they are doing compared to the projections in the study?

Answer: Using the maps that show rates of water-level declines, the landowners and water users can determine what the changes in water levels are in their area and what they are projected to be in the future. This can be accomplished by finding the approximate location of their property on the map pertaining to the year in question and by reading the estimates of water-level changes which are recorded in feet. To determine how he is doing from year to year, the landowner or water user can make measurements of depth to water in his own wells or obtain copies of measurements made by the Department for his area. These measurements can then be compared to the projected values on the map nearest the year of interest to obtain an estimate of the effectiveness of the conservation efforts.

NATURE OF THE OGALLALA AQUIFER

Because thorough understanding of the Ogallala aquifer is not necessary for the water user, the following discussion of aquifer geology and hydrology is rather general. Readers interested in pursuing the subject in more detail may do so from the numerous reports which have been published on the Ogallala. Most of these publications are included in the list of selected references of this report.

General Geology

Fresh ground water in Dawson and Borden Counties is obtained principally from the Ogallala Formation of Pliocene age. Water in the Ogallala

Formation is unconfined and is contained in the pore spaces of unconsolidated or partly consolidated sediments.

The Ogallala Formation principally consists of interfingering bodies of fine to coarse sand, gravel, silt, and clay—material eroded from the Rocky Mountains which was carried southeastward and deposited by streams. The earliest sediments, mainly gravel and coarse sand, filled the valleys cut in the pre-Ogallala surface. Pebbles and cobbles of quartz, quartzite, and chert are typical of these early sediments. After filling the valleys, deposition continued until the entire area that is now the Texas High Plains was covered by sediments from the shifting streams.

The upper part of the formation contains several hard, caliche-cemented, erosionally resistant beds called the "caprock". A wind-blown cover of fine silt, sand, and soil overlies the caprock.

The Ogallala deposits overlie rocks of lower permeability of Triassic and Cretaceous ages. On a broad scale, the erosional surface at the top of the Triassic and Cretaceous rocks dip gently (about 10 feet per mile [2m/km]) toward the southeast, similar to the slope of the land surface. In general, however, this pre-Ogallala surface had greater relief than the present land surface. Low hills and wide valleys which contain deep, narrow stream channels are typical features of the Triassic erosional surface. The Cretaceous rocks, being more resistant to erosion, remain as small buried mesas or buttes. Because the Ogallala was deposited on top of this irregular surface, the formation is very thin in some areas and very thick in others. Often this contrast occurs in relatively short distances.

The Triassic rocks, principally shale, serve as a nearly impermeable floor for the aquifer, but the buried mesas or buttes of Cretaceous rocks, where these are present, generally can yield water to wells. At these locations the Ogallala and Cretaceous waters are in hydrologic continuity; therefore, the water-yielding Cretaceous rocks are considered to be part of the Ogallala aquifer.

The Canadian River has cut deeply through the Ogallala Formation in the northern part of the Texas High Plains area. The valley effectively separates the formation geographically into two units having little hydraulic interconnection. Erosion has also removed the Ogallala from much of its former extent to the east, and to the west in New Mexico. As a result, the Southern High Plains, although relatively flat, stands in high relief and is hydraulically independent of adjacent areas. For this reason, coupled with the scarcity of local rainfall,

water that is being withdrawn from the aquifer cannot be replaced quickly by natural recharge and is in effect being mined.

Storage Properties

The coefficient of storage of an aquifer is defined as the volume of water released from or taken into storage per unit surface area of the aquifer per unit change in the component of head normal to that surface. In water-table aquifers such as the Ogallala, the coefficient of storage is nearly equal to the specific yield, which is defined as the quantity of water that a formation will yield under the force of gravity, if it is first saturated and then allowed to drain, the quantity of water being expressed as a percentage of the volume of the material drained.

A coefficient of storage of 15 percent has been selected for use in this study based on past studies and the results of numerous aquifer tests published in Texas Water Development Board Report 98 (Myers, 1969). The following chart shows the volumes of water corresponding to various amounts of aquifer saturated thickness, based on a storage coefficient of 15 percent. These are the approximate amounts of water that would drain from the aquifer material by gravity flow if the entire saturated thickness could be drained.

SATURATED THICKNESS (feet)	VOLUME OF WATER IN STORAGE (acre-feet, per surface acre)
25	3.75
50	7.50
75	11.25
100	15.00
150	22.50
200	30.00
250	37.50
300	45.00
400	60.00
500	75.00

Natural Recharge and Irrigation Recirculation

Recharge is the addition of water to an aquifer by either natural or artificial means. Natural recharge results chiefly from infiltration of precipitation. The Ogallala aquifer receives natural recharge by precipitation that falls within the county boundaries and in adjoining areas.

The amount and rate of natural recharge from precipitation depend on the amount, distribution, and intensity of the precipitation; the amount of moisture in

the soil when the rain or snowmelt begins; and the temperature, vegetative cover, and permeability of the materials at the site of infiltration. Because of the wide variations in these factors, it is difficult to estimate the amount of natural recharge to the ground-water reservoir. Estimates of annual natural recharge to the Ogallala aquifer made by Barnes and others (1949, p. 26-27) indicate only a fraction of an inch. Theis (1937, p. 546-568) suggested less than half an inch, and Havens (1966, p. F1), in a study of the Ogallala in New Mexico, indicated about 0.8 inch (2 cm) per year.

The authors of this report believe that recharge from precipitation may be more than these earlier estimates, due to changes in the soil and land surface that have accompanied large-scale irrigation development in the area. Some of the farming practices which are believed to have altered the recharge rate are: clearing the land of deep-rooted native vegetation; deep plowing of fields, which eliminates compacted zones in the soil (locally called "hard pans"), and the plowing of playa lake bottoms and sides; bench leveling, contour farming, and terracing; maintaining a generally higher soil moisture condition by application of irrigation water prior to large rains; and increasing the humus level in the root zone by plowing under a large amount of foliage from crops grown under irrigation.

Obtaining a reliable estimate of the present recharge rate is further complicated by the consideration which must be given to irrigation recirculation. A substantial portion of the water pumped from the Ogallala for irrigation percolates back to the aquifer. This does not constitute an additional supply of water, but reduces the net depletion of the aquifer. As with natural recharge, many factors are involved in making estimates of recirculation. Some of these factors are the rate, amount, and type of irrigation application; the soil type and the infiltration rate of the soil profile in the root zone; the amount of moisture in the soil prior to the irrigation application; the type of crop being grown, its root development, and its moisture extraction pattern; and the climatic conditions during and following the irrigation application. Tentative estimates of the actual amounts of recharge and irrigation recirculation in Dawson and Borden Counties will be found in a subsequent section on "Calculating Pumpage".

PROCEDURES USED TO OBTAIN PROJECTIONS

Hydrologic Data Base

The Texas Department of Water Resources maintains a network of water level observation wells in

Dawson and Borden Counties. Records from these wells provided the principal data base used in this study. This data base was supplemented in some areas with records from water well drillers' logs collected by the Department.

The data base included: (1) measurements of the depth to water below land surface, which have been made annually in the wells in the observation network; (2) the dates these measurements were made; and (3) the depth from land surface to the base of the Ogallala aquifer (In many cases, this was identical to the well depth). To facilitate automatic data processing with modern, high-speed computers, the data base also included a unique number for each well and the geographical coordinates of each well location.

Wells chosen from the data base for use in obtaining projections of future conditions were those in which depth to the base of the aquifer could be determined or estimated, and those needed to provide spaced data coverage in the two counties. Locations of the wells that were selected and used for control are shown on the various maps in this report.

Projecting the Depletion of Saturated Thickness

The water-use patterns between 1960 and 1972 as reflected in the changes in water levels in wells measured in the High Plains of Texas were used as the principal data source for developing an aquifer depletion schedule. The depletion schedule generally reflects average precipitation and precipitation distribution in the area for the duration of the study period. Additionally, in developing and applying the depletion schedule, adjustments through time were made to reflect the effects of depletion of the aquifer on its ability to yield water. That is, as the aquifer's saturated thickness decreases, its ability to yield water to wells is reduced, the well yields decline, less water is pumped, and there results a lessened rate of further aquifer depletion.

The aquifer's hydraulics are such that if a well penetrates the total saturated section and the pump is sized to produce the maximum the aquifer will yield, the well yield will decline at a disproportionately greater rate than the reduction in saturated thickness. Actually, the remaining well yield expressed as a percentage of former yield will be only about half of the remaining saturated thickness expressed as a percentage of former thickness. For example, a well with 80 feet (24.3 m) of saturated section and a maximum yield of 800 gallons per minute (50.4 l/s) will probably yield only 200

gallons per minute (12.6 l/s) when the saturated section is reduced to 40 feet (12.1 m).

The depletion schedule for Dawson, Borden, and surrounding counties was developed in the following manner:

1. The records for all water level observation wells for the years 1960 through 1972 in Andrews, Borden, Dawson, Gaines, Cochran, Garza, Hockley, Lubbock, Lynn, Terry and Yoakum Counties were separated from the master file. These counties have similar soil types, cropping patterns, depths to water, saturated thickness, and climatic conditions.
2. These well records were then sorted into groups according to the saturated thickness in each well as of 1966 (the middle year). Each group included records of all wells in a 20-foot (6.1-meter) range of saturated thickness. (Ranges are shown in the tabulation below.)
3. The average decline in water level was calculated for each year for each well group, and these decline values were adjusted to remove the effects of each year's deviation from long-term average precipitation.
4. The average annual decline in water level for the total period (1960-72) was calculated for each well group, incorporating the adjustments for departure from average precipitation.

From the foregoing procedure, the following depletion schedule was developed (no depletion was allowed for areas with 10 feet or less of saturated thickness):

RANGE OF SATURATED THICKNESS (feet)	AVERAGE ANNUAL WATER-LEVEL DECLINE, 1960-72 (feet)
0 to 10	0.00
10 to 20	.35
20 to 40	.74
40 to 60	.94
60 to 80	1.11
80 to 100	1.26
100 to 120	1.28
120 to 140	1.30
140 to 160	2.00
160 to 180	3.00
180 to 200	3.31
200 to 220	3.31
220 to 240	3.31
240 to 260	3.31
260 to 280	3.31

Based on this depletion schedule, a computer program was written to calculate future saturated thickness at individual well sites. The following problem is presented to show the computational procedures used.

Problem: A well has a saturated thickness of 110 feet in 1974 and one wants to project what the saturated thickness will be in this well for every year to the year 2020.

- Factors:
1. The beginning saturated thickness is 110 feet in 1974.
 2. The average decline rate is 1.28 feet per year for wells with saturated sections of 100 to 120 feet.
 3. The average decline rate is 1.26 feet per year for wells with saturated sections of 80 to 100 feet.

4. The average decline rate is 1.11 feet per year for wells with saturated sections of 60 to 80 feet.
5. The average decline rate is 0.94 foot per year for wells with saturated sections of 40 to 60 feet.
6. The average decline rate is 0.74 foot per year for wells with saturated sections of 20 to 40 feet.
7. The average decline rate is 0.35 foot per year for wells with saturated sections of 10 to 20 feet.
8. The time interval is 1974 through 2020.

The projected saturated thicknesses in the subject well are calculated and shown in the following table:


YEAR	SATURATED THICKNESS, BEGINNING OF YEAR (feet)	AVERAGE DECLINE RATE (feet)	SATURATED THICKNESS, END OF YEAR, (feet)
1974	110.00	1.28	108.72
1975	108.72	1.28	107.44
1976	107.44	1.28	106.16
1977	106.16	1.28	104.88
1978	104.88	1.28	103.60
1979	103.60	1.28	102.32
1980	102.32	1.28	101.04
1981	101.04	1.28	99.76
1982	99.76	1.26	98.50
1983	98.50	1.26	97.24
1984	97.24	1.26	95.98
1985	95.98	1.26	94.72
1986	94.72	1.26	93.46
1987	93.46	1.26	92.20
1988	92.20	1.26	90.94
1989	90.94	1.26	89.68
1990	89.68	1.26	88.42
1991	88.42	1.26	87.16
1992	87.16	1.26	85.90
1993	85.90	1.26	84.64
1994	84.64	1.26	83.38
1995	83.38	1.26	82.12
1996	82.12	1.26	80.86
1997	80.86	1.26	79.60
1998	79.60	1.11	78.49
1999	78.49	1.11	77.38
2000	77.38	1.11	76.27
2001	76.27	1.11	75.16
2002	75.16	1.11	74.05
2003	74.05	1.11	72.94
2004	72.94	1.11	71.83
2005	71.83	1.11	70.72
2006	70.72	1.11	69.61
2007	69.61	1.11	68.50
2008	68.50	1.11	67.39
2009	67.39	1.11	66.28
2010	66.28	1.11	65.17
2011	65.17	1.11	64.06

YEAR	SATURATED THICKNESS, BEGINNING OF YEAR (feet)	AVERAGE DECLINE RATE (feet)	SATURATED THICKNESS, END OF YEAR (feet)
2012	64.06	1.11	62.95
2013	62.95	1.11	61.84
2014	61.84	1.11	60.73
2015	60.73	1.11	59.62
2016	59.62	.94	58.68
2017	58.68	.94	57.74
2018	57.74	.94	56.80
2019	56.80	.94	55.86
2020	55.86	.94	54.92

Similar computations were made for each of the selected data-control wells in Dawson and Borden Counties, and the saturated thickness values for 1974, 1980, 1990, 2000, 2010, and 2020 were extracted from this data set for use in further calculations and mapping.


Mapping Saturated Thickness, and Calculating Volume of Water in Storage

To obtain estimates of the volume of water in storage in the Ogallala aquifer, an electronic digital computer was used to construct maps which reflect the saturated thickness of the aquifer for those years included in the study. These maps were then refined by the computer to reflect the number of acres corresponding to each range of saturated thickness. The number of acres for each range was multiplied by the saturated thickness in feet for that range and then by the coefficient of storage (0.15 or 15 percent), to yield an estimate of the volume of water in storage in each saturated-thickness range. Totaling these volumes produced an estimate of the volume of water in storage in each county. The current (1974) and projected volume estimates are shown in the following graphs:



Year	Acre-Feet
1974	3,640,000
1980	3,290,000
1990	2,730,000
2000	2,240,000
2010	1,800,000
2020	1,450,000

Estimated Volume of Water in Storage in Dawson County



Year	Acre-Feet
1974	220,000
1980	190,000
1990	160,000
2000	140,000
2010	120,000
2020	110,000

Estimated Volume of Water in Storage in Borden County

Preparing a data base and writing the necessary programs for the computer to use in constructing the saturated-thickness maps and in making the necessary calculations is time consuming; however, once the data base is prepared and programs written, the computer can perform in a few hours calculations that would have required many years of manual effort.

A generalized description of the methodology used in mapping and in computing water volume follows: A base map with a scale of 1 inch equals 2 miles (1:125,000) was selected to prepare data for computer processing. All data points (observation wells) were plotted on these base maps by hand and assigned identifying numbers. A machine called a *digitizer* was then used to translate these mapped location data (well locations, county boundaries, etc.) into information processible by the computer. To accomplish this, a latitude and longitude coordinate was recorded on each base map as a central reference point, and all data points and county boundaries were then digitized; that is, measurements were made by the digitizer to reference these data points and boundaries to the initial latitude and longitude coordinate. Then the digitized information was processed by the computer and the maps were re-created by a computer-driven plotter. The computer-plotted image maps were ultimately checked against the hand-constructed maps to verify that the data were plotted accurately.

The assignment of a unique number to each data point (observation well) on the base maps made it possible to machine process the data related to these points and to plot these data back on the maps at the proper location.

To compute the volume of water in storage, the computer was instructed to subdivide the counties into squares measuring approximately 0.5 mile (0.8 km). The known saturated-thickness values obtained from the data points were filled into the squares in which the data points were located. Based on these known values, the computer filled in a weighted-average value for each remaining square, taking into consideration all known values within a radius of 7 miles (11 km). After this step

was completed, the computer then counted the numbers of squares having equal values, thus obtaining the approximate area in square miles (later converted to acres) corresponding to each range of saturated thickness. As previously stated, the number of acres in each 25-foot (7.6-meter) range of saturated thickness was multiplied by the corresponding saturated-thickness value and the storage coefficient (0.15 or 15 percent) to obtain the approximate volume of water in acre-feet in that saturated-thickness range.

Although the calculations were made by the computer from information stored in its image field, the data in the image field were printed out in the form of contoured saturated-thickness maps, which are reproduced in this report. Facing each saturated-thickness map in the report are corresponding tabulations of the approximate volume of water in storage in each county.

Calculating Pumpage

Estimates of current pumpage were obtained in this study by calculating the storage capacity of the dewatered section of the Ogallala aquifer as reflected in changes in the annual depth-to-water measurements made in the water level observation wells. Factors for natural recharge and irrigation recirculation were then added to these volumetric figures to obtain more realistic pumpage estimates.

The step-by-step procedure involved in making pumpage estimates is similar to the procedures used in calculating the estimates of volume of water in storage; therefore, a more general explanation follows.

Change in water level (decline) maps for the aquifer were made by the computer for the years considered. From these maps, the volume of desaturated material was multiplied by the number of acres corresponding to each 0.25-foot (.076-meter) range of decline and then multiplied by the storage coefficient of the aquifer (0.15 or 15 percent), which resulted in an estimate of the volume of water taken from storage for each decline range. Estimates for natural recharge and irrigation recirculation were added to these values to obtain estimates of pumpage.

An attempt was made to obtain a reliable estimate of the natural recharge and recirculation for use in this study. This involved obtaining an estimate of the amount of water required by each of the major crops grown in the area. These values, generally referred to as "duty of water", were obtained from Texas Agricultural Experiment Stations located in the High Plains area. The


duty of water figure for each major crop was multiplied by the number of crop acres, and the resulting numbers were added together to yield an estimate of the total crop water demand.

The amount of precipitation which fell just prior to and during the growing season was subtracted from the total water demand estimate. The difference between these values should equal that amount which would have been supplied by irrigation, which will be referred to as irrigation makeup water.


The volume figure represented by the dewatered section was then compared to the volume of water which should have been supplied to crops by irrigation makeup water. In all tests, the volume of water represented by the depletion of the aquifer was considerably less than the makeup water estimate. This difference was attributed to irrigation recirculation and natural recharge.

Various combinations of estimates for natural recharge and recirculation were added to the volume represented by aquifer depletion, in an attempt to obtain comparable values with the makeup water estimated for the test years. One inch (2.54 cm) per year for natural recharge added to the volume represented by the depletion of the aquifer, and then adding 20 percent of this for recirculation, most nearly equaled the makeup water estimated in the largest number of instances in Dawson and Borden Counties and in adjoining counties with similar conditions.

These amounts were added to the previously calculated storage capacity of the dewatered section to obtain estimates for current (1974) and future pumpage. The following graphs show the current and projected estimates of pumpage for each county:



Estimated Pumpage in Dawson County



Estimated Pumpage in Borden County

Calculating Pumping Lifts

The pumping lift (pumping level) is the depth from land surface to the water level in a pumping well; it is equal to the depth of the static water level plus the drawdown due to pumping. The amount of pumping lift largely determines the amounts of energy required to produce the water, and thus strongly affects the pumping costs.

In calculating pumping lifts, procedures were used that are similar to those used in making estimates of the volume of water in storage and the estimates of pumpage. Again, the computer and original data base were used as previously described.

In making estimates of pumping lifts, it was assumed (1) that the yield of each pumping well is 800 gallons per minute (50.4 l/s) except as limited by the capacity of the aquifer (this conforms with the historical trend of equipping new wells with 8-inch [20-centimeter] or smaller pumps), (2) that the specific well yield is 10 gallons per minute per foot of drawdown (20.7 [l/s]/m), and (3) that once the well yield equals the capacity of the aquifer, the well will continue to be produced at a rate near the capacity of the aquifer until pumping lifts are within 10 feet (3 m) of the base of the aquifer. After that time, it is assumed that the pumping lift will remain constant because of greatly diminished well yields. It should be noted that this 10-foot (3-meter) minimum is somewhat arbitrarily chosen, as one cannot predict accurately the minimum saturated thickness that will be feasible for producing irrigation water under future economic conditions.

The above assumptions restrict the drawdown in wells to a maximum of 80 feet (24.3 m); that is, the maximum well yield of 800 gallons per minute (50.4 l/s) divided by specific well yield of 10 gallons per minute per foot (2.07 [l/s]/m) equals 80 feet (24.3 m) of maximum drawdown.

Based on the above assumptions, pumping lifts were calculated separately for each of the selected data-control wells in the counties. The factors involved were the historical and projected saturated-thickness values, the historical and projected static water levels, and the drawdown value assigned to the Dawson and Borden County area.

In all areas where the aquifer's saturated thickness was 90 feet (27.4 m) or greater (areas where a well, pumped at full capacity, would be drawn down 80 feet [24.3 m] to yield 800 gallons per minute [50.4 l/s]), the computer was instructed to add 80 feet (24.3 m)—the drawdown—to the static water level to

determine pumping lift. For a well with a saturated thickness of less than 90 feet (27.4 m), the pumping lift was calculated by subtracting 10 feet (3 m) from the depth of the well (base of the aquifer). These calculations were made for each year of record to be reported (1974, 1980, 1990, 2000, 2010, and 2020) for each well. The pumping-lift values were stored in the computer and printed out in the form of contour maps. Additionally, the surface area corresponding to each interval between the mapped contours was calculated and printed out in tabular form.

Well-Yield Estimates

Estimates of the rate, in gallons per minute, at which the Ogallala aquifer should be capable of yielding water to wells in various areas of the two counties are presented on maps for each year of record reported (1974, 1980, 1990, 2000, 2010, and 2020). These well-yield estimates are based on capabilities of the aquifer to yield water to irrigation wells of prevailing construction as reflected by the very large number of pumping tests which have been conducted in various saturated-thickness intervals in the Texas High Plains. The estimates are adjusted to reflect the expected decreases in well yields through time due to the reduced saturated thickness as depletion of the aquifer progresses.

The well-yield estimates are subject to deviations caused by localized geological conditions. The Ogallala is not a homogeneous formation; that is, the silt, clay, sand, and gravel which generally comprise the formation vary from place to place in thickness of layers, layering position, and grain-size sorting. The physical composition of the formation material can drastically affect the ability of the formation to yield water to wells. As an example, in areas where the saturated portion of the formation is comprised of thick beds of coarse and well-sorted grains of sand, the well yields probably will exceed the estimates shown on the maps. In other localized areas, the saturated portion of the formation may be comprised principally of thick beds of silt and clay which can be expected to restrict well yields to less than those shown on the maps.

The following can be used as a general guide in Dawson and Borden Counties in estimating well yields based on saturated thickness:

SATURATED THICKNESS (feet)	WELL YIELD (gallons per minute)
Less than 20	Less than 100
20 to 40	100 to 250

SATURATED THICKNESS
(feet)

40 to 60
60 to 80
80 to 100
More than 100

WELL YIELD
(gallons per minute)

250 to 500
500 to 800
800 to 1,000
More than 1,000

The maps presented in this report are intended for use as general guidelines only and are not recommended for use in determining water availability when buying and selling specific tracts of land. Inasmuch as the availability of ground water constitutes a large portion of the price of land bought and sold in this area, it is recommended that a qualified ground-water hydrologist be consulted to make appraisals of ground-water conditions when such transactions are contemplated.

DISTINCTION BETWEEN PROJECTIONS AND PREDICTIONS

The actions of the Dawson and Borden County water user will determine whether the projections of this study come to pass, as the rate of depletion of the

ground-water resource is determined by the rate of water use. The authors have not made predictions of what will occur, but have furnished projections based on past trends and presently available information.

There are many unpredictable factors which can influence the future rates of withdrawal of ground water from the Ogallala aquifer for irrigation farming. These factors include: (1) the amounts and distribution of precipitation which will be received in the area in the future; (2) federal crop acreage controls or the lack of these; (3) the price and demand for food and fiber grown in the area; (4) the cost and availability of energy to produce water from the aquifer; (5) farm labor cost and availability of farm labor; (6) results of continuing research that seeks to develop more frugal water-application methods for irrigation, crops having less water demand, and methods for inducing clouds to yield more water as rain; and (7) most important, the degree to which feasible soil and water conservation measures are employed by the High Plains irrigator. Any of these factors could appreciably influence the rate of use of ground water in the future; however, the projections in this study provide a reasonable set of general expectations on the further depletion of the aquifer.

SATURATED THICKNESS AND VOLUME OF
WATER IN THE OGALLALA AQUIFER

1974

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Dawson County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	66,870	184,369
25- 50	150,464	848,883
50- 75	157,504	1,443,812
75-100	80,294	1,014,723
100-125	9,343	152,064
TOTAL	464,475	3,643,851


1974

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Borden County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	26,527	68,959
25- 50	17,297	86,014
50- 75	3,819	34,690
75-100	1,847	23,627
100-125	506	7,854
TOTAL	49,996	221,144




EXPLANATION

Well used for control

150

Line showing approximate saturated thickness of the Ogallala aquifer, in feet.

Interval is 25 feet (7.62m)



1974
Estimated Saturated Thickness

1980

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Dawson County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	89,779	242,699
25- 50	169,865	971,057
50- 75	152,259	1,400,141
75-100	48,568	609,096
100-125	4,004	64,601
TOTAL	<u>464,475</u>	<u>3,287,594</u>


1980

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Borden County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	33,549	81,828
25- 50	11,243	57,259
50- 75	3,358	30,479
75-100	1,679	21,537
100-125	167	2,565
TOTAL	<u>49,996</u>	<u>193,668</u>



EXPLANATION

Well used for control

— 15.0

Line showing approximate saturated thickness of the Ogallala aquifer, in feet.

Interval is 25 feet (7.62m)



1980
Projected Saturated Thickness

1990

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Dawson County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	130,785	335,735
25- 50	202,016	1,140,407
50- 75	113,649	1,032,199
75-100	17,357	215,132
100-125	668	10,242
TOTAL	<u>464,475</u>	<u>2,733,715</u>

1990

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Borden County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	38,959	87,595
25- 50	7,176	37,630
50- 75	2,686	23,957
75-100	1,175	14,622
TOTAL	<u>49,996</u>	<u>163,804</u>

2000

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Dawson County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	183,356	455,441
25- 50	206,344	1,118,048
50- 75	69,936	606,110
75-100	4,839	59,182
TOTAL	<u>464,475</u>	<u>2,238,781</u>


2000

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Borden County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	41,057	83,853
25- 50	6,253	33,246
50- 75	2,183	20,108
75-100	503	6,007
TOTAL	<u>49,996</u>	<u>143,214</u>



2000
Projected Saturated Thickness

2010

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Dawson County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0- 25	256,301	607,235
25- 50	180,967	960,072
50- 75	26,372	225,561
75-100	835	9,619
TOTAL	<u>464,475</u>	<u>1,802,487</u>


2010

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Borden County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0-25	43,112	80,758
25-50	5,037	27,126
50-75	1,847	17,009
TOTAL	<u>49,996</u>	<u>124,893</u>



2010
Projected Saturated Thickness

2020

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Dawson County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0-25	328,637	727,606
25-50	127,493	648,964
50-75	8,345	70,180
TOTAL	<u>464,475</u>	<u>1,446,750</u>


2020

Volume of Water in Storage Corresponding
to Mapped Saturated-Thickness Intervals

Borden County

(Coefficient of Storage: 15 percent)

<u>MAPPED SATURATED- THICKNESS INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>VOLUME OF WATER IN STORAGE (acre-feet)</u>
0-25	44,118	77,199
25-50	4,703	24,670
50-75	1,175	10,139
TOTAL	<u>49,996</u>	<u>112,008</u>



EXPLANATION

●
Well used for control


— 150 —
Line showing approximate saturated thickness of the Ogallala aquifer, in feet.



Interval is 25 feet (7.62m)



2020
Projected Saturated Thickness

POTENTIAL WELL YIELD OF THE
OGALLALA AQUIFER








EXPLANATION

Potential well yields, in gallons per minute

less than 100	500-800
100-250	800-1000
250-500	more than 1000


1980
Projected Potential Yield






- EXPLANATION**
- Potential well yields, in gallons per minute
- less than 100
 - 100-250
 - 250-500
 - 500-800
 - 800-1000
 - more than 1000

2000
Projected Potential Yield



2010
Projected Potential Yield



PUMPING LIFTS IN THE OGALLALA AQUIFER

1974

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Dawson County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	17,758
25- 50	31,045
50- 75	16,671
75-100	54,907
100-125	98,261
125-150	113,413
150-175	90,440
175-200	32,073
200-225	3,006
225-250	2,004
250-275	1,007
TOTAL	<u>460,585</u>

1974

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Borden County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	6,770
25- 50	26,681
50- 75	12,946
75-100	3,190
100-125	<u>167</u>
TOTAL	49,754

1980

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Dawson County


<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	17,644
25- 50	28,632
50- 75	16,347
75-100	54,331
100-125	96,933
125-150	110,738
150-175	91,773
175-200	33,741
200-225	4,009
225-250	2,505
250-275	1,006
TOTAL	<u>457,659</u>

1980

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Borden County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	10,846
25- 50	26,711
50- 75	8,915
75-100	2,854
100-125	503
TOTAL	<u>49,829</u>



EXPLANATION

- Well used for control
- 200 — Line showing approximate pumping lift, in feet.
- Interval is 25 feet (7.62m)

1980
Projected Pumping Lifts

1990

Surface Area Corresponding To Mapped
Pumping-Lift Intervals

Dawson County


<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	20,674
25- 50	25,383
50- 75	15,803
75-100	54,331
100-125	96,265
125-150	108,567
150-175	90,773
175-200	36,411
200-225	5,011
225-250	2,338
250-275	1,341
TOTAL	<u>456,897</u>

1990

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Borden County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	8,972
25- 50	28,143
50- 75	9,486
75-100	2,015
100-125	1,007
TOTAL	<u>49,623</u>



EXPLANATION

- Well used for control
- 200 — Line showing approximate pumping lift, in feet.
- - - - Interval is 25 feet (7.62m)

1990
Projected Pumping Lifts

2000

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Dawson County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	17,310
25- 50	28,769
50- 75	16,544
75-100	54,331
100-125	96,098
125-150	107,564
150-175	88,769
175-200	38,583
200-225	5,846
225-250	2,505
250-275	1,340
TOTAL	<u>457,659</u>

2000

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Borden County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	6,770
25- 50	25,337
50- 75	13,115
75-100	2,854
100-125	1,511
125-150	167
TOTAL	<u>49,754</u>




EXPLANATION

• Well used for control

— 200 —

Line showing approximate pumping lift, in feet.

Interval is 25 feet (7.62m)



**2000
Projected Pumping Lifts**

2010

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Dawson County


<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	17,310
25- 50	28,769
50- 75	16,544
75-100	54,331
100-125	95,931
125-150	107,564
150-175	88,769
175-200	38,750
200-225	5,345
225-250	3,006
250-275	1,340
TOTAL	<u>457,659</u>

2010

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Borden County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	6,770
25- 50	25,337
50- 75	13,115
75-100	2,854
100-125	1,511
125-150	167
TOTAL	<u>49,754</u>



2010
Projected Pumping Lifts

2020

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Dawson County


<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	17,310
25- 50	28,769
50- 75	16,544
75-100	54,331
100-125	95,931
125-150	107,564
150-175	88,769
175-200	38,750
200-225	5,345
225-250	3,006
250-275	1,340
TOTAL	<u>457,659</u>

2020

Surface Area Corresponding to Mapped
Pumping-Lift Intervals

Borden County

<u>MAPPED PUMPING-LIFT INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>
0- 25	6,770
25- 50	25,337
50- 75	13,115
75-100	2,854
100-125	1,511
125-150	167
TOTAL	<u>49,754</u>



2020
Projected Pumping Lifts

PUMPAGE FROM THE OGALLALA AQUIFER

1974

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Dawson County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	92,320	1,418	10,934
.25- .50	87,497	4,916	14,646
.50- .75	72,806	6,856	15,508
.75-1.00	117,369	15,352	30,159
1.00-1.50	66,719	11,121	20,017
1.50-2.00	161	43	68
2.00-3.00	162	59	87
TOTAL	437,034	39,765	91,419

1974

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Borden County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	33,132	435	3,832
.25- .50	11,245	543	1,776
.50- .75	1,341	121	280
.75-1.00	584	70	143
TOTAL	46,302	1,169	6,031



1980

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Dawson County


<u>MAPPED DECLINE-RATE INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)</u>	<u>ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)</u>
0.00-0.25	19,299	403	2,411
.25- .50	48,672	2,913	8,363
.50- .75	84,897	8,136	18,253
.75-1.00	174,973	23,239	45,384
1.00-1.50	135,866	22,709	40,838
TOTAL	463,707	57,400	115,249

1980

Pumpage Corresponding to Mapped
Decline-Rate Intervals


Borden County

<u>MAPPED DECLINE-RATE INTERVAL (feet)</u>	<u>SURFACE AREA (acres)</u>	<u>STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)</u>	<u>ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)</u>
0.00-0.25	14,283	236	1,710
0.25- .50	12,863	724	2,155
0.50- .75	12,995	1,211	2,753
0.75-1.00	9,352	1,187	2,360
TOTAL	49,493	3,358	8,978



EXPLANATION

- Well used for control
- 1.25 —
- Line showing approximate rate of decline in water level, in feet per year.
- Interval is variable



1980
Projected Rates of Water-Level Decline

1990

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Dawson County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	41,046	817	5,082
.25- .50	70,065	4,082	11,905
.50- .75	83,371	7,962	17,892
.75-1.00	178,662	23,508	46,076
1.00-1.50	90,006	14,731	26,678
TOTAL	463,150	51,100	107,633

1990

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Borden County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	18,844	279	2,217
.25- .50	17,841	964	2,941
.50- .75	8,806	815	1,858
.75-1.00	3,022	374	751
TOTAL	48,513	2,432	7,767




EXPLANATION

- Well used for control
- 1.25

Line showing approximate rate of decline in water level, in feet per year.

Interval is variable



1990
Projected Rates of Water-Level Decline

2000

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Dawson County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	48,708	1,042	6,120
.25- .50	79,060	4,421	13,211
.50- .75	102,890	10,073	22,377
.75-1.00	200,386	25,862	51,073
1.00-1.50	28,683	4,627	8,420
TOTAL	459,727	46,025	101,201

2000

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Borden County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	21,048	312	2,479
.25- .50	18,739	986	3,057
.50- .75	6,208	578	1,314
.75-1.00	2,350	295	589
TOTAL	48,345	2,171	7,439

2010

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Dawson County


MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	87,214	1,645	10,693
.25- .50	105,043	5,820	17,489
.50- .75	133,132	12,812	28,688
.75-1.00	120,697	15,436	30,593
1.00-1.50	11,850	1,902	3,468
TOTAL	457,936	37,615	90,931

2010

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Borden County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	31,537	416	3,650
.25- .50	12,611	658	2,051
.50- .75	3,190	293	671
.75-1.00	1,007	128	254
TOTAL	48,345	1,495	6,626



EXPLANATION

Well used for control

Line showing approximate rate of decline in water level, in feet per year.

Interval is variable

2010
Projected Rates of Water-Level Decline

2020

Pumpage Corresponding to Mapped
Decline-Rate Intervals

Dawson County


MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	148,282	2,266	17,544
.25- .50	110,278	6,165	18,426
.50- .75	111,230	10,522	23,750
.75-1.00	68,223	8,527	17,055
1.00-1.50	3,486	548	1,006
TOTAL	441,499	28,028	77,781

2020

Pumpage Corresponding to Mapped
Decline-Rate Intervals


Borden County

MAPPED DECLINE-RATE INTERVAL (feet)	SURFACE AREA (acres)	STORAGE CAPACITY OF DEWATERED SECTION (acre-feet)	ESTIMATED PUMPAGE RATE INCLUDING NATURAL RECHARGE AND IRRIGATION RECIRCULATION (acre-feet per year)
0.00-0.25	36,877	395	4,161
.25- .50	6,505	347	1,067
.50- .75	2,518	228	525
.75-1.00	1,007	125	251
TOTAL	46,907	1,095	6,004



EXPLANATION

- Well used for control
- 1.25 — Line showing approximate rate of decline in water level, in feet per year. Interval is variable



2020
Projected Rates of Water-Level Decline

ACKNOWLEDGEMENTS

Special appreciation is expressed to the Dawson and Borden County landowners and water users for allowing their wells to be measured by Department personnel. This study could not have been accomplished without their cooperation and the records obtained from their wells.

Additionally, appreciation is expressed to several individuals for consultation and for review and comment on the methodology and techniques employed in this study: Mr. Frank A. Rayner, former general manager of the High Plains Underground Water Conservation District No. 1; Dr. Donald Reddell, associate professor of Engineering, Texas A&M University; Mr. Leon New, irrigation specialist, Texas Agriculture Extension Service, Lubbock, Texas; Mr. Shelby Newman, superintendent, Texas Agricultural Experiment Station, Stephenville, Texas; Dr. C. C. Reeves, Jr., associate professor of Geosciences, Texas Tech University; and Dr. James Osborn, former chairman of the Department of Agricultural Economics, Texas Tech University.

STAFF INVOLVEMENT

This report is one of a series of county reports being published under the title "Analytical Study of the Ogallala Aquifer". Former staff member A. Wayne Wyatt was instrumental in initiating the study and coauthored a number of the previously published reports of this series.

The Dawson and Borden County report was prepared under the supervision of Bernard B. Baker, chief of the Data Branch in the Texas Department of Water Resources' Ground Water Division, Dr. Tommy R. Knowles, director. Numerous staff members of this Division assisted the authors in assembling and

evaluating data and information. Overall technical supervision of the Ogallala study is exercised by C. R. Baskin, director, Data and Technical Review. The Department's Information Systems and Services office, David L. Ferguson, director, provided automated data processing and computational services, and prepared the manuscript copy of tabular and graphical displays.

METRIC CONVERSIONS TABLE

For those readers interested in using the International System (SI) of Units, the metric equivalents of English units of measurement have been given in parenthesis in the text. The English units used in tables of this report may be converted to metric units by the following conversion factors:

MULTIPLY ENGLISH UNITS	BY	TO OBTAIN SI UNITS
inches	2.540	centimeters (cm)
feet	.3048	meters (m)
miles	1.609	kilometers (km)
square miles	2.590	square kilometers (km ²)
gallons	3.785	liters (l)
gallons per minute	.06309	liters per second (l/s)
gallons per minute per foot	.207	liters per second per meter ([l/s]/m)
acre-feet	1,233.	cubic meters (m ³)
acre-feet	1.233 X 10 ⁻⁶	cubic kilometers (km ³)
million acre-feet	1.233	cubic kilometers (km ³)

SELECTED REFERENCES

- Alexander, W. H., Jr., 1961, Geology and ground-water resources of the Northern High Plains of Texas, progress report no. 1: Texas Board Water Engineers Bull. 6109, 47 p.
- Alexander, W. H., Jr., Broadhurst, W. L., and White, W. N., 1943, Progress report on ground water in the High Plains in Texas: Texas Board Water Engineers duplicated rept., 22 p.
- Baker, C. L., 1915, Geology and underground waters of the northern Llano Estacado: Univ. Texas Bull. 57, 225 p.
- Baker, E. T., Jr., Long, A. T., Jr., Reeves, R. D., and Wood, L. A., 1963, Reconnaissance investigation of the ground-water resources of the Red River, Sulphur River, and Cypress Creek basins, Texas: Texas Water Comm. Bull. 6306, 137 p.
- Barnes, J. R., and others, 1949, Geology and ground water in the irrigated region of the Southern High Plains of Texas, progress report no. 7: Texas Board Water Engineers duplicated rept., 51 p.
- Bell, A. E., and Sechrist, A. W., 1970, Playas—Southern High Plains of Texas: Playa Lake Symposium, ICASALS, Texas Tech Univ., Lubbock, Texas, Oct. 1970, Proc., p. 35-39.
- Brand, J. P., 1953, Cretaceous of Llano Estacado of Texas: Univ. Texas, Bur. Econ. Geology Rept. of Inv. 20, 59 p.
- Broadhurst, W. L., Sundstrom, R. W., and Weaver, D. E., 1949, Public water supplies in western Texas: Texas Board Water Engineers duplicated rept., 277 p.
- _____, 1951, Public water supplies in western Texas: U.S. Geol. Survey Water-Supply Paper 1106, 168 p.
- Cronin, J. G., 1961, A summary of the occurrence and development of ground water in the Southern High Plains of Texas: Texas Board Water Engineers Bull. 6107, 110 p.
- _____, 1969, Ground water in the Ogallala Formation in the Southern High Plains of Texas and New Mexico: U.S. Geol. Survey Hydrol. Inv. Atlas HA-330, 9 p.
- Cronin, J. G., Follett, C. R., Shafer, G. H., and Rettman, P. L., 1963, Reconnaissance investigation of the ground-water resources of the Brazos River basin, Texas: Texas Water Comm. Bull. 6310, 163 p.
- Cronin, J. G., and Wells, L. C., 1960, Geology and ground-water resources of Hale County, Texas: Texas Board Water Engineers Bull. 6010, 146 p.
- Evans, G. L., and Meade, G. E., 1945, Quaternary of the Texas High Plains *in* Contributions to geology, 1944: Univ. Texas Pub. 4401, p. 485-507.
- Fenneman, N. M., 1931, Physiography of the western United States: New York, McGraw-Hill Book Co., 534 p.
- Fink, B. E., 1963, Ground-water geology of Triassic deposits, northern part of the Southern High Plains of Texas: High Plains Underground Water Conservation Dist. No. 1, Rept. 163, 79 p.
- Frye, J. C., 1970, The Ogallala Formation—a review: Ogallala Aquifer Symposium, Texas Tech Univ., Lubbock, Texas, 1970, Proc., p. 5-14.
- Frye, J. C., and Leonard, A. B., 1957, Studies of Cenozoic geology along eastern margin of Texas High Plains, Armstrong to Howard Counties: Univ. Texas, Bur. Econ. Geology Rept. of Inv. 32, 62 p.
- Gammon, S. W., and Muse, W. R., 1966, Water-level data from observation wells in the Southern High Plains of Texas: Texas Water Devel. Board Rept. 21, 537 p.
- Gard, Chris, 1958, Ground-water conditions in Carson County, Texas: Texas Board Water Engineers Bull. 5802, 120 p.
- Gillett, P. T., and Janca, I. G., 1965, Inventory of Texas irrigation, 1958 and 1964: Texas Water Comm. Bull. 6515, 317 p.
- Gould, C. N., 1906, The geology and water resources of the eastern portion of the Panhandle of Texas: U.S. Geol. Survey Water-Supply Paper 154, 64 p.
- _____, 1907, The geology and water resources of the western portion of the Panhandle of Texas: U.S. Geol. Survey Water-Supply Paper 191, 70 p.

- Grubb, H. W., 1966, Importance of irrigation water to the economy of the Texas High Plains: Texas Water Devel. Board Rept. 11, 53 p.
- Haragan, D. R., 1970, An investigation of clouds and precipitation for the Texas High Plains: Texas Water Devel. Board Rept. 111, 125 p.
- Havens, J. S., 1966, Recharge studies on the High Plains in Northern Lea County, New Mexico: U.S. Geol. Survey Water-Supply Paper 1819-F, 52 p.
- Hughes, W. F., and Harman, W. L., 1969, Projected economic life of water resources, Subdivision no. 1, High Plains underground water reservoir: Texas A&M Univ. Tech. Mon. 6, 82 p.
- Lang, J. W., and Twichell, Trigg, 1945, Water resources of the Lubbock district, Texas: Texas Board Water Engineers duplicated rept., 168 p.
- Leggat, E. R., 1952, Geology and ground-water resources of Lynn County, Texas: Texas Board Water Engineers Bull. 5207, 76 p.
- _____, 1954a, Summary of ground-water development in the Southern High Plains, Texas: Texas Board Water Engineers Bull. 5402, 21 p.
- _____, 1954b, Ground-water development in the Southern High Plains of Texas, 1953: Texas Board Water Engineers Bull. 5410, 7 p.
- _____, 1957, Geology and ground-water resources of Lamb County, Texas: Texas Board Water Engineers Bull. 5704, 187 p.
- Long, A. T., Jr., 1961, Geology and ground-water resources of Carson County and part of Gray County, Texas, progress report no. 1: Texas Board Water Engineers Bull. 6102, 45 p.
- Luckey, R. R., and Hofstra, W. E., 1974, Digital model of the Ogallala aquifer of the northern part of the Northern High Plains of Colorado: Colorado Water Conservation Board, Colorado Water Resources Circ. No. 24, 22 p.
- McAdoo, G. D., Leggat, E. R., and Long, A. T., 1964, Geology and ground-water resources of Carson County and part of Gray County, Texas, progress report no. 2: Texas Water Comm. Bull. 6402, 30 p.
- Moulder, E. A., and Frazor, D. R., 1957, Artificial-recharge experiments at McDonald well field, Amarillo, Texas: Texas Board Water Engineers Bull. 5701, 34 p.
- Myers, B. N., 1969, Compilation of results of aquifer tests in Texas: Texas Water Devel. Board Rept. 98, 537 p.
- New, Leon, 1968, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 14 p.
- _____, 1969, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 14 p.
- _____, 1970, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 10 p.
- _____, 1971, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 16 p.
- _____, 1972, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 18 p.
- _____, 1973, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 16 p.
- _____, 1974, High Plains irrigation survey: Texas A&M Univ. Ext. Service duplicated rept., 18 p.
- North Plains Ground Water Conservation District No. 2, 1966, Geology and ground-water resources of the North Plains Ground Water Conservation District No. 2: North Plains Ground Water Conservation District No. 2, Progress rept. No. 2, 49 p.
- _____, 1970, Geology and ground-water resources of the North Plains Ground Water Conservation District: North Plains Ground Water Conservation District No. 2, Progress rept. No. 3, 35 p.
- _____, 1973, Geology and ground-water resources of Lipscomb County, Texas: North Plains Ground Water Conservation District No. 2, 31 p.
- Osborn, J. E., Harris, T. R., and Owens, T. R., 1974, Impact of ground-water and petroleum on the economy of the Texas High Plains: Texas Tech Univ., Dept. Agr. Econ., 87 p.
- Rayner, F. A., 1965, The ground water supplies of the Southern High Plains of Texas: Proc. 3rd West Texas Water Conf., Texas Tech Coll., p. 20-42.
- _____, 1973, Taking a new look at the demise of the Ogallala aquifer: Testimony presented to West Texas Citizens Advisory Council on Water Resources public hearing, Lubbock, Texas, October 3, 1973, 16 p.
- Rettman, P. L., and Leggat, E. R., 1966, Ground-water resources of Gaines County, Texas: Texas Water Devel. Board Rept. 15, 186 p.

- Schwiesow, W. F., 1965, Playa lake use and modification in the High Plains, *in* Studies of playa lakes in the High Plains of Texas: Texas Water Devel. Board Rept. 10, p. 1-8.
- Sherrill, D. W., 1958, High Plains irrigation survey: Texas A&M Coll. Ext. Service duplicated rept., 10 p.
- _____, 1959, High Plains irrigation survey: Texas A&M Coll. Ext. Service duplicated rept., 10 p.
- Smith, J. T., 1973, Ground-water resources of Motley and northeastern Floyd Counties, Texas: Texas Water Devel. Board Rept. 165, p. 8.
- Swann, T., 1974, Texas High Plains facts: Lubbock. Water, Inc., 10 p.
- Texas Board Water Engineers, 1960, Reconnaissance investigation of the ground-water resources of the Canadian River basin, Texas: Texas Board Water Engineers Bull. 6016, 33 p.
- Texas Water Development Board, 1971, Inventories of irrigation in Texas, 1958, 1964, and 1969: Texas Water Devel. Board Rept. 127, 232 p.
- Theis, C. V., 1937, Amount of ground-water recharge in the Southern High Plains: Am. Geophys. Union Trans., 18th Ann. Mtg., p. 564-568.
- Thurmond, R. V., 1951, High Plains irrigation survey: Texas A&M Coll. Ext. Service duplicated rept., 4 p.
- White, W. N., Broadhurst, W. L., and Lang, J. W., 1946, Ground water in the High Plains of Texas: U.S. Geol. Survey Water-Supply Paper 889-F, p. 381-420.
- Wyatt, A. W., 1968, Progress report no. 1, A general discussion accompanied by hydrological maps pertaining to the ground-water resources in the South Plains Underground Water Conservation District No. 4: South Plains Underground Water Conservation District No. 4, 24 p.
- _____, 1975, TWDB High Plains study shows 340 million acre-feet of water in 45-county area, *in* Water for Texas: Texas Water Devel. Board pub., V. 5, no. 1 and 2, p. 20-22.
- Wyatt, A. W., and others, 1970, Water-level data from observation wells in the Southern High Plains of Texas, 1965-70: Texas Water Devel. Board Rept. 121, 361 p.
- Wyatt, A. W., and others, 1971, Water-level data from observation wells in the Northern Panhandle of Texas: Texas Water Devel. Board Rept. 137, 263 p.
- Wyatt, A. W., Bell, A. E., and Morrison, S., 1976, Analytical study of the Ogallala aquifer in Hale County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 200, 63 p.
- _____, 1976, Analytical study of the Ogallala aquifer in Lamb County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 204, 63 p.
- _____, 1976, Analytical study of the Ogallala aquifer in Parmer County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 205, 63 p.
- _____, 1976, Analytical study of the Ogallala aquifer in Castro County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 206, 63 p.
- _____, 1976, Analytical study of the Ogallala aquifer in Bailey County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 207, 63 p.
- _____, 1976, Analytical study of the Ogallala aquifer in Crosby County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 209, 63 p.
- _____, 1976, Analytical study of the Ogallala aquifer in Floyd County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 211, 63 p.
- _____, 1977, Analytical study of the Ogallala aquifer in Briscoe County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 212, 63 p.
- _____, 1977, Analytical study of the Ogallala aquifer in Deaf Smith County, Texas—projections of saturated thickness, volume of water in storage, pumpage rates, pumping lifts, and well yields: Texas Water Devel. Board Rept. 213, 63 p.

