RECEIVED
MAY 0 2 2019
TWDB CONTRACTS

Final Report

Guadalupe Blanco River Authority

Early Warning System – San Marcos Watershed in Caldwell County, Texas

TWDB Contract No. 1600012042

December 28, 2018

Ms. Sarah Hustead Texas Water Development Board PO Box 13231 Austin, TX 78711-3231

Re:

TWDB Contract No. 1600012042

Early warning system Report - San Marcos Watershed in Caldwell County

Dear Ms. Hustead:

Transmitted herewith is our first draft of the Early Warning System Report – San Marcos Watershed in Caldwell County, Texas.

This report includes a Table of Contents, Scope of Work, Equipment Installed and List of Figures as set out in Contract No. 1600012042.

Please contact me should you have any questions or require any additional information to finalize the reporting requirements

Sincerely,

Thomas D. Hill, P.E.

Ih 0 91 M

Chief Engineer



Main Office: 933 East Court Street ~ Seguin, Texas 78155 830-379-5822 ~ 800-413-4130 ~ 830-379-9718 fax ~ www.gbra.org

TABLE OF CONTENTS

Letter of Transmittal
Table of contents
Scope of Work
List of Figures

I.	Intro	duction	
	A.	General	1
	B.	Scope of Work	2-4
		LIST OF FIGURES	
I.	Area	Map	
	A-1	Rainfall Gauge Placement Map for New Installs in Caldwell County	5
	A-2	All Rainfall Gauge Coordinates in Caldwell County	6
	A-3	Placement Map of all Installed Rainfall Gauges in Caldwell County	7
	B-1	Rain Gauge Installed – Sunset Trail	8
	B-2	Rain Gauge Installed – Chuck Wagon Road	9
	B-3	Rain Gauge Installed – Taylorsville Road at Elm Creek	10
	B-4	Rain Gauge Installed – Liberty Lane	11
	B-5	Rain Gauge Installed – Grandpa Road	12
	B-6	Rain Gauge Installed – Rolling Ridge	13
	B-7	Rain Gauge Installed – Tower Road	14
	B-8	Rain Gauge Installed – Acorn Road	15
	C-1	Siren Placement Map – Martindale, Caldwell County	
		a. Area Acoustic Coverage	16
	C-2	Siren Placement Site 1 Martindale, Caldwell County	17
	C-3	Siren Placement Site 2 Martindale, Caldwell County	18
	D-1	Public Information	
		a. GBRA Rain Gauge Reports published on web-site	19
		b. Texas Water Development Board TexMesonet	20

LIST OF ACRONYMS

EMC – Emergency Management Coordinator
GBRA – Guadalupe Blanco River Authority
HADS – Hydrometeorological Automated Data System
LCRA – Lower Colorado River Authority
NEMA – National Electrical Manufacturers Association
NWS – National Weather Service
NWS/FAA – National Weather Service/Federal Aviation Administration

USGS – United Stated Geological Survey

NWS-RFC - National Weather Service River Forecast Center

SCADA - Supervisory Control and Data Acquisition

EAA – Edwards Aquifer Authority

RAINFALL SCADA CALDWELL COUNTY

INTRODUCTION

A. General Purpose

The areas all along the San Marcos River watershed have seen considerable growth. With rapidly developing communities bringing concerns about the increasing threat of flooding and associated damages due to increased urbanization. These areas have been hit hard affecting many populated areas, scenic and environmental resources since major flood events in 1998, 2002, the Memorial Day Flooding in May 2015 and again on October 30, 2015.

The Texas Hill County is known as "Flash Flood Alley". This area is the most flash flood-prone in the state, and among the most flood-prone areas in the country. Much like other flash flood-prone communities across the country, the geography in this region can rapidly transform the rivers and creeks in the Hill Country into raging tidal surges of water, mud and debris that is capable of taking out entire homes, businesses, roads and bridges.

The purpose of this project provided additional rainfall gauges to an early warning system in the watershed of the San Marcos River by expanding it into Caldwell County. Using existing supervisory control and data acquisition (SCADA) system, the Guadalupe-Blanco River Authority (GBRA) network incorporated these gauges into their monitoring network. The real-time monitoring of the rainfall gauges allows for a rapid response to changing conditions, reducing losses and improving the overall efficiency in notifying City Officials and Emergency Management Coordinators (EMC) and officers of potential flooding.

The Blanco - Memorial Day Flood of 2015 brought to light the need to improve metrological data collection within the watershed. Due to the steep terrain of the upper watershed, floodwaters peak higher and travel faster than most rivers. The high growth rate of the region, and the accompanying additions of impervious cover leading to runoff of floodwaters in major rain events, increases the potential for additional loss of life in the future for residents and those coming to the area for recreational activities.

B. SCOPE OF WORK

The project sets out to expand the existing GBRA rainfall network into Caldwell County. The existing GBRA rainfall program was created to provide a data collection platform with the Guadalupe River Watershed to support flooding monitoring and flood forecasting efforts by the National Weather Service (NWS) and local emergency responders. The network in Caldwell County assists in improved forecasting and warning dissemination along the San Marcos River watershed by (1) an expansion of the rainfall telemetry network in Caldwell County, TX and (2) the installation of warning sirens in the City of Martindale.

Additional rain gauges maintained by other entities located in Caldwell County are shown in Figures "A-2" and "A-3". These gauges are sponsored by Hydrometeorological Automated Data System (HADS); Lower Colorado River Authority (LCRA); and National Weather Service/Federal Aviation Administration (NWS/FAA).

Type of Rain Gauge Equipment:

The eight rainfall gauging sites utilized equipment which was consistent with the existing GBRA rainfall network. Each rain gauge site consisted of a 6 inch diameter tipping bucket rain gauge Model TR-525 by Texas Electronics, Inc., a SCADA-Pack Model 201 programmable logic controller with a built-in Freewave Radio and a Yagi antenna. Power was provide by a 50 watt solar panel and 75 amp-hour battery. The battery has the electrical storage capacity to last 6 or 7 days with minimal sunlight.

The equipment was placed in a NEMA 4 Electrical metal box and mounted on a vertical 4 inch diameter galvanized pole which transitioned to a 3 inch pole at the top. The electrical enclosure equipment was placed 6 to 7 feet above the ground to minimize vandalism. The solar panel, tipping bucket and Yagi antenna was located toward the top of the pole.

Outdoor Siren Equipment:

Federal Signal Model 2001-130 Siren was purchased for alerting citizens of the City of Martindale of an impending flood event on the San Marcos River. The system consists of two outdoor warning sirens located adjacent to the San Marcos River. The siren locations were selected based on a) obtaining right of way from willing property owners and b) source of 240 volt power circuits and c) appropriate acoustic levels to reach most homes within the flood prone areas. The first site is located 600 feet North West of Martindale City Hall while the second site is 9000 feet North West of City Hall. See Figure C-1 for area location map-siren locations.

The Outdoor warning siren system consists of a 50 foot pole, antenna, radio-styled and omnidirectional siren. The radio is a VHF radio that interfaces with the Caldwell County Sheriff's radio system. The Model 2001-130 omni-directional siren utilizes an AC/DC motor, controlled with battery backup in the event of a power failure.

Siting of Rainfall Gauges

A number of factors were used to select the gauge locations including:

- a) Maintain spacing between gauges to 5 or 6 miles.
- b) Insure an unobstructed radio frequency path to the site,
- c) The ease of obtaining right of way for the equipment.
- d) A site location which provides ease of access for maintenance.

A review of past studies suggested rain gauges should be spaced approximately 7 to 8 miles apart. Due to the compact nature of storm events in Central Texas, a spacing of 5-6 miles was selected and used where possible. The map showing the location and coordinates for the rain gauges can be found in Figure "A-1", "A-2", and "A-3". Pictures of each rain gauge can be found in Figures "B-1" through "B-8".

Siting of Outdoor Sirens

The primary purpose of the siren is to warn homeowners within the flood plain along the San Marcos River in Martindale. The sirens were placed no further than ½ mile from the San Marcos River and no further than two miles from each other. The siren placement acoustic map can be found in Figure "C-1". Pictures of the two sirens can be found on Figures "C-2" and "C-3".

Use of Data

Rainfall data is available for use by a number of entities and include:

- a) County Road Administrator to identify and install flood road blockage of low water crossings
- b) County Emergency Management Coordinator (EMC) to assist with localized flooding issues.
- c) The NWS Forecast Office to help forecasters decide whether to issue flood and weather warning
- d) The NWS River Forecast Center in Fort Worth utilizes this data to assist with the calibration of NEXRAD weather radar rainfall estimates. This process is sometimes referred to as "ground-truthing."
- e) General Public to better prepare for a developing heavy rainfall event.

Access to Data

The rainfall-telemetry gauge reports every 6 minutes to the Master GBRA computer located in Seguin, Texas. A web report is published every 10 minutes in a tabular format. The data can be accessed from two sources:

- a) Data can be found at https://www.gbra.org/rain. The web report displays rainfall totals for every 1hour, 3-hour, 6-hour and 24-hour. See Figure "D-1a"
- b) The Caldwell county eight gauging sites along with the other GBRA gauging sites are also displayed on the TWDB TexMesonet web-site and can be found at https://www.texmesonet.org/.

TexMesonet provides access to rainfall data from not only GBRA but from Lower Colorado River Authority (LCRA), United Stated Geological Survey (USGS), Federal Aviation Administration (FAA), Edward Aquifer Authority (EAA) and City of Austin. See Figure "D-1b".

Maintenance

Rainfall sites will be visited at least every two to three months to check for visual signs of damages from high wind or vandals. The rain gauges will be inspected to insure the tipping bucket mechanism is not jammed. The battery will need to be checked at least once a year. The battery is expected to last for four to six years. The remaining equipment will have a life expectancy of twenty-five to thirty years.

RAINFALL GAUGE PLACEMENT MAP FOR NEW INSTALLS IN ALDWELL COUNTY WITH TWDB FUNDING FIGURE "A-1" AREA MAP




FIGURE "A-2"

ALL RAINFALL GAUGE COORDINATES IN CALDWELL COUNTY

Map Label	Station	Location Name	Latitude	Longitude
LCRA	LRCT2	Lockhart 6 NE - LCRA	30°7'46.9"N	97°53'47.4"W
		San Marcos, San Marcos Municipal Airport		
KHY1	KHY1	- NWS/FAA	29°53'54.24"N	97°52'0.83"W
LLGT2	LLGT2	San Marcos River Near Luling 1S - HADS	29°39'55.4"N	97°39'2.99"W
		San Marcos River Near Martindale 1SSW -		
SMRT2	SMRT2	HADS	29°50'3.46"N	97°50'18.64"W
GBR01	GBR01	Sunset Trail - GBRA	29°44'43.30"N	97°41′8.12"W
GBR02	GBR02	Chuck Wagon Road GBRA	29°45'28.91"N	97°30′17.20"W
GBR03	GBR03	Taylorville Road - GBRA	29°52′19.83"N	97°26′54.33"W
GBR04	GBR04	Liberty Lane - GBRA	29°55′27.34"N	97°34′44.51"W
GBR05	GBR05	Grandpa Road - GBRA	29°59′36.37"N	97°38′50.91"W
GBR06	GBR06	Rolling Ridge - GBRA	29°56′4.97"N	97°40′41.15"W
GBR07	GBR07	Tower Road - GBRA	29°51′28.65"N	97°45′5.96"W
GBR08	GBR08	Acorn Road - GBRA	29°46′33.71"N	97°43′16.68"W
GBR09	GBR09	Rogers Ranch Road - GBRA	29°58′28.85"N	97°43′51.11"W
GBR19	GBR19	FM 21 off FM 2720 - GBRA	29°56′35.57"N	97°47′56.88"W

FIGURE "A-3" AREA MAP

PLACEMENT MAP OF ALL INSTALLED RAINFALL GAUGES FOR CALDWELL COUNTY




FIGURE "B-1"
Rain Gauges Installed



GBRA – C-1
Sunset Trail
29°44'43.30"N 97°41'8.12"W

FIGURE "B-2" Rain Gauges Installed



GBRA – C-2
Chuck Wagon Road
29°45'28.91"N 97°30'17.20"W

FIGURE "B-3" Rain Gauges Installed



GBRA – C-3

Taylorsville Road at Elm Creek

29°52'19.83" N 97°26'54.33"W

FIGURE "B-4"
Rain Gauges Installed



GBRA – C-4 Liberty Lane

29°55'27.34"N 97°34'44.51"W

FIGURE "B-5"
Rain Gauges Installed



GBRA – C-5 Grandpa Road

29°59'36.37"N 97°38'50.91"W

FIGURE "B-6"
Rain Gauges Installed



GBRA – C-6
Rolling Ridge
29°56'4.97"N 97°40'41.15"W

FIGURE "B-7"
Rain Gauges Installed



GBRA – C-7 Tower Road 29°51'28.65"N 97°45'5.96"W

FIGURE "B-8" Rain Gauges Installed



GBRA - C-8

Acorn Road

29°46'33.71"N 97°43'16.68"W

Figure "C-1" - AREA MAP SIREN PLACEMENT ACOUSTIC ANALYSIS CALDWELL COUNTY





Figure "C-2" – MARTINDALE SIREN SITE 1
Behind Martindale Water Supply Corporation



Figure "C-3" – MARTINDALE SIREN SITE 2



"D-1a" - Public Information — Rain Gauge Reports www.gbra.org/rain



Rain Gauge Report Monday, October 8, 2018

3:42 PM CST (RTU Times Do Not Reflect Daylight Saving Time)

Note: Data is gathered by remote automated sensors and is posted without a quality check. GBRA assumes no responsibility for inaccuracy due to equipment failure. Interactive map. Comal and Guadalupe County rain gauge map (PDF)

0	Oleffer News	07117		otal (inches)		
County	Station Name	RTU Time	1-Hr	3-Нг	6-Hr	24-F
Caldwell	Over at Table	0.00.014	0.00	0.00		
	Sunset Trail	2:36 PM	0.00	0.00	0.01	0.0
	Chuck Wagon Rd	2:36 PM	0.00	0.03	0.03	0.0
	Taylorville Rd	2:36 PM	0.00	0.00	0.00	0.0
	Liberty Lane	2:36 PM	0.00	0.06	0.06	0.0
	Grandpa Rd	2:36 PM	0.00	0.09	0.09	0.0
	Rolling Ridge	2:36 PM	0.00	0.18	0.18	0.1
	Tower Rd	2:36 PM	0.00	0.00	0.06	0.0
	Acom Rd	2:36 PM	0.00	0.00	0.00	0.0
	Rogers Ranch Rd	2:36 PM	0.00	0.17	0.17	0.1
Comal				- History		
	GBRA Tower	2:29 PM	0.00	0.10	0.10	0.2
	Bear Creek	2:14 PM	0.00	0.00	0.00	0.0
	Startzville	2 48 PM	0.00	0.00	0.00	0.1
	Hoffman Road	2:44 PM	0.01	0.31	0.31	0.3
	Third Crossing	3 02 PM	0.00	0.01	0.01	0.2
	Waggner Ranch	2:17 PM	0.00	0.00	0.00	0.0
	Stenen Road	2.39 PM	0.00	0.00	0.00	0.
	Shadow Hills	3:17 PM	0.00	0.01	0.01	0.0
	NBU Tower on Geronimo Creek	2:30 PM				
			0.03	0.19	0.19	0.
	FM 3009 on Dry Comal Creek	2:30 PM	0.00	0.00	0.00	0.0
	Kruger Canyon Rd on Dry Comal	2:30 PM	0.00	0.00	0 00	0.0
Our dates	Bresky Road on Isaac Creek	2:30 PM	0.03	0.03	0.04	0.2
Guadalup						1200
	Seguin WTP	2:30 PM	0.00	0.11	0 11	0.
	Hwy 123 @ Geronimo Creek	2:30 PM	0.00	0.30	0.30	0.3
	Branch Road on Geronimo Creek	2:30 PM	0.04	0.07	0 10	0.
	FM 1044 on Young Creek	2:30 PM	0.00	0.06	0.06	0.3
	FM 1044 on Long Creek	2:30 PM	0.01	0.16	0.16	0,1
	FM 775 on Deadmans Creek	2:30 PM	0.02	0.16	0.16	0.
	Still Meadow Rd on Cottonwood Cr	2:31 PM	0.00	0.01	0.01	0.6
	Nash Creek Road on Darst Creek	2:31 PM	0.00	0.01	0.02	0.0
Hays						
	Hams Hill Rd	2:36 PM	0.00	0.00	0.05	0.0
	Bunton Lane	2:36 PM	0.01	0.01	0.03	0.0
	Engelke Rd	2:36 PM	0.00	0.25	0.25	0
	Hays Youth Complex	2:36 PM	0.00	0.01	0.19	0.1
	Sierra West Rd	2:36 PM	0.01	0.09	0 23	0.3
	Rocking M Rd	2:36 PM	0.00	0.07	0.86	0.4
	FM 21 off FM 2720	2.36 PM	0.00	0.00	0.01	0.1
	Long Horn Trail	2:37 PM	0.00	0.06	0.06	0.3
	ML Olive School Rd	2:37 PM	0.00	0.00	0.00	0.2
	Rim Rock Rd	2:37 PM	0.00	0.48	0.48	0.5
	TAIL LADEN FAU	2.3/ FM	0.00	U.46	V.96	US

Hulling TEXASFL COD org 00 e 00 C 8 7 3.5 3 50 00 e B Ma (Ma) g 80 6 1 1 1 1 (S) (E) inc. (S) 90 m 95 0 B 10.01 600 600 500 (500) (500) (a) (b) (c) 8 6 60 E 0.00 90 6

FIGURE "D-1b"
Public Information –
TXMesonet
https://www.texmesonet.org